

Kohtaki Dry Ice Former, Model Shirorenga 80

Mfg: Kohtaki

Model: Shirorenga 80

Stock No. tPPMI002.

Serial No.

Kohtaki Dry Ice Former. Model: Shirorenga 80. Produces 7 in. L x 3 in. W x 1-1/4 H dry-ice blocks within (3) stainless steel dies. Dry-ice process: CO₂ injection, pre-forming, compression, elevation, ejection. Unit features a Fuji Electric Counter and injection timer with a maximum set period of 60 sec. Removable access rear panels and top access cover allow for easy maintenance. Katakai Hydraulic Pump with 17-gallon reservoir tank. Mitsubishi Super Line Motor, 2.2 kW, 940/1120/1140 rpm, 200/200/220 V, 10.8/10/9.8 amps, 50/60/60 Hz, 3 phase. Inlets: (1) 1/2 in. dia. CO₂ line, (1) 4-1/2 in. pipe fitting. Outlets: (1) 8 in. W x 2-1/2 in. H dry ice outlet. Overall dimensions: 50 in. L x 28 in. W x 51 in. H. Acme Electric Corporation Power Transformer, Cat No: T-1-53008, .500 KVA, 1 phase, primary volts: 240x280, secondary volts 120/240 V, 50/60 Hz. (3) Omron WL Limit Switches, Model CN2-A2. (3) Hydraulic cylinders to push forward, push up, and eject. Pascal Pressure Switch, Model: SA400P. (2) Micro Switches, Model 1LS1.



